

DATA SHEET



Single Phase Induction Motor - Squirrel Cage

Customer :																																		
Product line : Rolled Steel Single-Phase			Product code : 15098626 Catalog # : 00536OS1C184T-S																															
Frame : 182/4T Output : 5 HP (3.7 kW) Poles : 2 Frequency : 60 Hz Rated voltage : 208-230 V Rated current : 21.5-19.3 A L. R. Amperes : 148-133 A LRC : 6.9x(Code G) No load current : 2.41-2.80 A Rated speed : 3495 rpm Slip : 2.92 % Rated torque : 1.04 kgfm Locked rotor torque : 290 % Breakdown torque : 250 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.0066 kgm ² Design : L			Locked rotor time : 10s (cold) 6s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Cooling method : IC01 - ODP Mounting : F-1 Rotation ¹ : Both (CW and CCW) Starting method : Direct On Line Approx. weight ³ : 31.0 kg																															
<table border="1"> <tr> <td>Output</td> <td>25%</td> <td>50%</td> <td>75%</td> <td>100%</td> </tr> <tr> <td>Efficiency (%)</td> <td>77.6</td> <td>78.7</td> <td>83.2</td> <td>84.0</td> </tr> <tr> <td>Power Factor</td> <td>0.81</td> <td>0.98</td> <td>0.99</td> <td>0.99</td> </tr> </table>			Output	25%	50%	75%	100%	Efficiency (%)	77.6	78.7	83.2	84.0	Power Factor	0.81	0.98	0.99	0.99	Foundation loads Max. traction : 38 kgf Max. compression : 70 kgf																
Output	25%	50%	75%	100%																														
Efficiency (%)	77.6	78.7	83.2	84.0																														
Power Factor	0.81	0.98	0.99	0.99																														
<table border="1"> <tr> <td></td> <td colspan="2"><u>Drive end</u></td> <td colspan="2"><u>Non drive end</u></td> </tr> <tr> <td>Bearing type</td> <td>:</td> <td>6206 ZZ</td> <td>:</td> <td>6205 ZZ</td> </tr> <tr> <td>Sealing</td> <td>:</td> <td>Without Bearing Seal</td> <td>:</td> <td>Without Bearing Seal</td> </tr> <tr> <td>Lubrication interval</td> <td>:</td> <td>-</td> <td>:</td> <td>-</td> </tr> <tr> <td>Lubricant amount</td> <td>:</td> <td>-</td> <td>:</td> <td>-</td> </tr> <tr> <td>Lubricant type</td> <td>:</td> <td colspan="3">Mobil Polyrex EM</td> </tr> </table>						<u>Drive end</u>		<u>Non drive end</u>		Bearing type	:	6206 ZZ	:	6205 ZZ	Sealing	:	Without Bearing Seal	:	Without Bearing Seal	Lubrication interval	:	-	:	-	Lubricant amount	:	-	:	-	Lubricant type	:	Mobil Polyrex EM		
	<u>Drive end</u>		<u>Non drive end</u>																															
Bearing type	:	6206 ZZ	:	6205 ZZ																														
Sealing	:	Without Bearing Seal	:	Without Bearing Seal																														
Lubrication interval	:	-	:	-																														
Lubricant amount	:	-	:	-																														
Lubricant type	:	Mobil Polyrex EM																																
Notes																																		
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																															
Rev.	Changes Summary			Performed	Checked	Date																												
Performed by																																		
Checked by					Page	Revision																												
Date	31/07/2023				1 / 1																													