DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				•	3	
Customer	:					
Product line : Rolled Steel NEMA Premium Efficien Three-Phase					Product code : Catalog # :	15379025 00118OT3E143T-SGH
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	9	: 143/51 : 1 HP (: 4 : 60 Hz : 230/46 : 3.02/1 : 24.2/1 : 8.0x(C : 1.92/0 : 1760 r : 2.22 % : 0.412 : 290 % : 360 % : H : 1.15 : 0.0046 : B	0.75 kW) 60 V .51 A 2.1 A code L) .958 A pm b kgfm		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 39s (cold) 22s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IC01 - ODP : F-1 : Both (CW and CCW) : 52.0 dB(A) : Direct On Line : 15.9 kg
Output		50%	75%	100%	Foundation loads	
Efficiency (%)	79.9 82.2 8 79.4 8		84.0 83.4 82.9	85.5 82.6 83.2	Max. traction	: 39 kgf
Power Factor	0.29 0.34 0	0.51 0.59			Max. compression	: 55 kgf
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type		: : V :	<u>Drive 6</u> 6205 Vithout Be - -	ZZ aring Seal	Non drive end 6203 ZZ Without Bearing Se - - bil Polyrex EM	al

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed		Checked	Date
Performed by						
Checked by					Page	Revision
Date	31/07/2023				1/1	